



Analog Technologies Inc. Price List as of 10/30/2009

Laser Drivers / Controllers	Page 2 & 3
LED Drivers / Controller & Power Supplies	Page 3
LED's - High Efficiency High Power and Ultra Bright	Page 3
LED's - Replacement Bulbs	Page 4
Thermistors	Page 4
TEC Drivers / Controllers	Page 4 - 6
TEC Modules	Page 6 & 7
SMD Component Kits	Page 7 - 9
Flashlights	Page 9

N = New
S = Special order
O = obsolete



Laser Drivers / Controllers

	Part Number	Description	1 - 9	10 - 49	50 - 199	200 - 499	≥500
	ATLS100MA103S	Ultra low noise laser controller 100ma with current limit - SMT	75.00	71.25	67.50	63.75	60.00
	ATLS100MA103D	Ultra low noise laser controller 100ma with current limit - DIP	75.00	71.25	67.50	63.75	60.00
	ATLS200MA103S	Ultra low noise laser controller 200ma with current limit - SMT	75.00	71.25	67.50	63.75	60.00
	ATLS200MA103D	Ultra low noise laser controller 200ma with current limit - DIP	75.00	71.25	67.50	63.75	60.00
	ATLS250MA103S	Ultra low noise laser controller 250ma with current limit - SMT	75.00	71.25	67.50	63.75	60.00
	ATLS250MA103D	Ultra low noise laser controller 250ma with current limit - DIP	75.00	71.25	67.50	63.75	60.00
	ATLS500MA103S	Ultra low noise laser controller 500ma with current limit - SMT	75.00	71.25	67.50	63.75	60.00
	ATLS500MA103D	Ultra low noise laser controller 500ma with current limit - DIP	75.00	71.25	67.50	63.75	60.00
	ATLS1A103S	Ultra low noise laser controller 1amp with current limit - SMT	75.00	71.25	67.50	63.75	60.00
	ATLS1A103D	Ultra low noise laser controller 1amp with current limit - DIP	75.00	71.25	67.50	63.75	60.00
	ATLS1A102-S	Very Low Noise Diode Laser Controller upto 1 amp output voltage 1.5v to 4.0v - SMT	75.00	71.25	67.50	63.75	60.00
	ATLS1A102-D	Very Low Noise Diode Laser Controller upto 1 amp output voltage 1.5v to 4.0v - DIP	75.00	71.25	67.50	63.75	60.00
O	ATLS1A102-D-L	switch mode driver disabled - DIP	75.00	71.25	67.50	63.75	60.00
O	ATLS1A102-S-L	switch mode driver disabled - SMT	75.00	71.25	67.50	63.75	60.00
	ATLS2A201-D	Constant Current Low Noise Laser Driver upto 2 amps, upto 2.5v output. DPSSL and EDFA - DIP	78.00	74.10	70.20	66.30	62.40
	ATLS4A201-D	Constant Current Low Noise Laser Driver upto 4 amps, upto 2.5v output. DPSSL and EDFA - DIP	85.00	80.75	76.50	72.25	68.00
	ATLS6A201-D	Constant Current Low Noise Laser Driver upto 6 amps, upto 2.5v output. DPSSL and EDFA - DIP	95.00	90.25	85.50	80.75	76.00
	ATLS2A202D	Constant Current CW Laser Driver. upto 2 amps low noise high efficiency. - DIP	88.00	83.60	79.20	74.80	70.40
	ATLS3A202D	Constant Current CW Laser Driver. upto 3 amps low noise high efficiency. - DIP	88.00	83.60	79.20	74.80	70.40
N	ATLS4A202D	Constant Current CW Laser Driver. upto 4 amps low noise high efficiency. - DIP	95.00	90.25	85.50	80.75	76.00
	ATLS4A212D	High Voltage 4.5V ~ 16V Constant Current Laser Driver upto 4 amps low noise high efficiency - DIP	72.00	68.40	64.80	61.20	57.60
	ATLS1A103DEV1.0	Evaluation board for ATLS200MA103, ATLS250MA103, ATLS500MA103, and ATLS1A103. for "D" package	25.00	22.50			
	ATLSXA201DEV1.0	Constant Current Laser Driver Evaluation board Rev 1.0 for ATLS1A201D, ATLS2A201D and ATLS3A201D,	42.00	38.00			
N	ATLS202DEV1.0	Constant Current Laser Driver Evaluation board Rev 1.0 for ATLS2A202D, ATLS3A202D, ATLS4A202D and ATLS6A201D	42.00	38.00			
	ATLD10A5-DEV1.0	10 A High Efficiency Laser Controller Eval. Board	90.00	85.5	81.00	76.50	72.00
			1-4	5-24	25-99	100-499	≥500
	ATLD10A5-D	10A High Efficiency Laser Controller DIP package	248.00	235.60	223.20	210.80	198.40
	ATLD10A5-S	10A High Efficiency Laser Controller SMD package	248.00	235.60	223.20	210.80	198.40
			1-9	10-49	50-249	250-499	≥500



AAS6V40A2	High Efficiency AC input 40A 6V Laser Driver pin 11= 5v	228.00	216.60	205.20	193.80	182.40
AAS6V40A2SN	High Efficiency AC input 40A 6V Laser Driver pin 11 = synco	228.00	216.60	205.20	193.80	182.40
AAS6V70A2	High Efficiency AC input 70A 6V Laser Driver pin 11= 5v	560.00	532.00	504.00	476.00	448.00
AAS6V70A1SN	High Efficiency AC input 70A 6V Laser Driver pin 11 = synco	560.00	532.00	504.00	476.00	448.00
CWD-01-V2-D	High Efficiency Constant Current Diode Laser Controller	88.00	83.60	79.20	74.80	70.40
LDA1-CP1	Constant Current and Constant Power Laser Driver - P type diode	110.00	104.50	99.00	93.50	88.00
LDA1-CP2	Constant Current and Constant Power Laser Driver - N type diode	110.00	104.50	99.00	93.50	88.00

LED Drivers / Controller

Part Number	Description	1 - 9	10 - 49	50 - 199	200 - 499	≥500
ABK36V1A1W	Controller of fixed 1A output in TO-220 package, Wire leads	20.80	19.76	18.72	17.68	16.64
ABK36FR35A1W	Controller of fixed 0.35A output in TO-220 package, Wire leads	20.80	19.76	18.72	17.68	16.64
ABK36VF7A1W	Controller of fixed 0.70A output in TO-220 package, Wire leads	20.80	19.76	18.72	17.68	16.64
ABK36VF1A1W	Controller of fixed 1A output in TO-220 package, Wire leads	20.80	19.76	18.72	17.68	16.64
ABK36V1A1	Controller of fixed 1A output in TO-220 package, PCB connector	19.80	18.81	17.82	16.83	15.84
ABK36VFR35A1	Controller of fixed 0.35A output in TO-220 package, PCB connector	19.80	18.81	17.82	16.83	15.84
ABK36VF7A1	Controller of fixed 0.70A output in TO-220 package, PCB connector	19.80	18.81	17.82	16.83	15.84
ABK36VF1A1	Controller of fixed 1A output in TO-220 package, PCB connector	19.80	18.81	17.82	16.83	15.84
LED22V1A700MA	Input voltage 7V to 22V, output 700ma, driving one to two 5W Luxeon LED	19.00	18.05	17.10	16.15	15.20
AAS50V0P35A1	Electronic power supply designed for driving a series of LEDs with a 350mA constant current.	22.00	20.90	19.80	18.75	17.60

LED's - High Efficiency High Power and Ultra Bright

		1 - 9	10 - 49	50 - 199	200-499	≥500
ALED1WNWL60RI	1W, natural white, 60°, Front Emitting, 90 to 1000 Lumen	6.30	5.98	5.67	5.35	5.05
ALED1WNWL80RI	1W, natural white, 80°, Front Emitting, 90 to 1000 Lumen	6.30	5.98	5.67	5.35	5.05
ALED1WNWL120RI	1W, natural white, 120°, Front Emitting, 90 to 1000 Lumen	6.30	5.98	5.67	5.35	5.05
ALED1WNWL140RI	1W, natural white, 140°, Front Emitting, 90 to 1000 Lumen	6.30	5.98	5.67	5.35	5.05
ALED1WNWS160RI	1W, natural white, 160°, Front Emitting, 90 to 1000 Lumen	6.30	5.98	5.67	5.35	5.05
ALED1WNWS160PI-ST	1W, natural white, 160°, Front Emitting, 80 to 90 Lumen	7.80	7.41	7.02	6.63	6.25
ALED1WNWL60PI	1W, natural white, 60°, Side Emitting, 80 to 90 Lumen	5.20	4.95	4.68	4.42	4.16
ALED1WNWL80PI	1W, natural white, 80°, Side Emitting, 80 to 90 Lumen	5.20	4.95	4.68	4.42	4.16
ALED1WNWL120PI	1W, natural white, 120°, Side Emitting, 80 to 90 Lumen	5.20	4.95	4.68	4.42	4.16
ALED1WNWL140PI	1W, natural white, 140°, Side Emitting, 80 to 90 Lumen	5.20	4.95	4.68	4.42	4.16
ALED1WNWS160PI	1W, natural white, 160°, Side Emitting, 80 to 90 Lumen	5.20	4.95	4.68	4.42	4.16



LED's - Replacement Bulbs

SILVERLED-1N6V	Replacement LED bulbs for PR12 and PR13 incandescent bulbs, input voltage 2.4V to 6V, > 40% longer lasting	12.00	11.40	10.80	10.20	9.60
SILVERLED-1N8V	Replacement LED bulbs for PR12 and PR13 incandescent bulbs, input voltage 4.75V to 8V, > 40% longer lasting	11.00	10.45	9.90	9.35	8.80

Thermistors

		1 - 9	10 - 49	50 - 199	200-499	≥ 500
ATH10KL2	high precision (+/-0.25C@25C) 10K lugged	5.80	5.51	5.22	4.93	4.64
ATH100KL2	high precision (+/-0.25C@25C) 100K lugged	5.80	5.51	5.22	4.93	4.64
ATH10KR8	high precision (+/-0.25C@25C) 10K bare	4.80	4.56	4.32	4.08	3.84
ATH100KR8	high precision (+/-0.25C@25C) 100K bare	4.80	4.56	4.32	4.08	3.84

TEC Drivers / Controllers

		1 - 9	10 - 49	50-199	200-499	≥ 500
TECA1-LD5V-5V-D	5v power supply, - 5V TEC - internal compensation network - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-LD5V-4V-D	5v power supply, - 4V TEC - internal compensation network - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-LD5V-3.5V-D	5v power supply, - 3.5V TEC - internal compensation network - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-LD5V-3.0V-D	5v power supply, - 3.0V TEC - internal compensation network - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-LD5V-2.5V-D	5v power supply, - 2.5V TEC - internal compensation network - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-LD5V-2V-D	5v power supply, - 2VTEC - internal compensation network - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-LD3V-3.0V-D	3.3v power supply, - 3.0V TEC - internal compensation network - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-LD3V-2.5V-D	3.3v power supply, - 2.5V TEC - internal compensation network - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-LD3V-2.0V-D	3.3v power supply, - 2V TEC - internal compensation network - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-5V-5V-D	5v power supply, 5V across TEC - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-5V-4V-D	5v power supply, 4V across TEC - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-5V-3.5V-D	5v power supply, 3.5V across TEC - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-5V-3.0V-D	5v power supply, 3.0V across TEC - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-5V-2.5V-D	5v power supply, 2.5V across TEC - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-5V-2V-D	5v power supply, 2V across TEC - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-3V-3.0V-D	3.3v power supply, 3.0V across TEC - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-3V-2.5V-D	3.3v power supply, 2.5V across TEC - DIP	81.00	76.95	72.90	68.85	64.80
TECA1-3V-2.0V-D	3.3v power supply, 2.0V across TEC - DIP	81.00	76.95	72.90	68.85	64.80
TECA1LD-5V-5V-S	5v power supply, 5V TEC - internal compensation network -SMT	81.00	76.95	72.90	68.85	64.80
TECA1LD-5V-4V-S	5v power supply, 4V TEC - internal compensation network -SMT	81.00	76.95	72.90	68.85	64.80



TECA1LD-5V-3.5V-S	5v power supply, 3.5V TEC - internal compensation network -SMT	81.00	76.95	72.90	68.85	64.80
TECA1LD-5V-3.0V-S	5v power supply, 3.0V TEC - internal compensation network -SMT	81.00	76.95	72.90	68.85	64.80
TECA1LD-5V-2.5V-S	5v power supply, 2.5V TEC - internal compensation network -SMT	81.00	76.95	72.90	68.85	64.80
TECA1LD-5V-2V-S	5v power supply, 2V TEC - internal compensation network -SMT	81.00	76.95	72.90	68.85	64.80
TECA1LD-3V-3.0V-S	5v power supply, 3.0V TEC - internal compensation network - SMT	81.00	76.95	72.90	68.85	64.80
TECA1LD-3V-2.5V-S	5v power supply, 2.5V TEC - internal compensation network - SMT	81.00	76.95	72.90	68.85	64.80
TECA1LD-3V-2V-S	5v power supply, 2V TEC - internal compensation network - SMT	81.00	76.95	72.90	68.85	64.80
TECA1-5V-5V-S	5v power supply, 5V across TEC - SMT	81.00	76.95	72.90	68.85	64.80
TECA1-5V-4V-S	5v power supply, 4V across TEC - SMT	81.00	76.95	72.90	68.85	64.80
TECA1-5V-3.5V-S	5v power supply, 3.5V across TEC - SMT	81.00	76.95	72.90	68.85	64.80
TECA1-5V-2.5V-S	5v power supply, 2.5V across TEC - SMT	81.00	76.95	72.90	68.85	64.80
TECA1-5V-2V-S	5v power supply, 2V across TEC - SMT	81.00	76.95	72.90	68.85	64.80
TECA1-3V-3.0V-S	3v power supply, 3.0V across TEC - SMT	81.00	76.95	72.90	68.85	64.80
TECA1-3V-2.5V-S	3v power supply, 2.5V across TEC - SMT	81.00	76.95	72.90	68.85	64.80
TECA1-3V-2V-S	3v power supply, 2V across TEC - SMT	81.00	76.95	72.90	68.85	64.80
TEC5V4A-D	Max. output current: 4A voltage across TEC 5.0V internal net.- DIP	95.00	90.25	85.50	80.75	76.00
TEC4V4A-D	Max. output current: 4A voltage across TEC 4.0V internal net. - DIP	95.00	90.25	85.50	80.75	76.00
TEC3.5V4A-D	Max. output current: 4A voltage across TEC 3.5V internal net. - DIP	95.00	90.25	85.50	80.75	76.00
TEC3V4A-D	Max. output current: 4A voltage across TEC 3.0V internal net. - DIP	95.00	90.25	85.50	80.75	76.00
TEC2.5V4A-D	Max. output current: 4A voltage across TEC 2.5V internal net. - DIP	95.00	90.25	85.50	80.75	76.00
TEC2.0V4A-D	Max. output current: 4A voltage across TEC 2.0V internal net. - DIP	95.00	90.25	85.50	80.75	76.00
TEC6A101D5V	Max Output current 6 A, internal net. voltage across TEC 5.0V - DIP	105.00	99.75	94.50	89.25	84.00
TEC6A101D4V	Max Output current 6 A, internal net. voltage across TEC 4.0V - DIP	105.00	99.75	94.50	89.25	84.00
TEC6A101D3.5V	Max Output current 6 A, internal net. voltage across TEC 3.5V - DIP	105.00	99.75	94.50	89.25	84.00
TEC6A101D3V	Max Output current 6 A, internal net. voltage across TEC 3.0V - DIP	105.00	99.75	94.50	89.25	84.00
TEC6A101D2.5V	Max Output current 6 A, internal net. voltage across TEC 2.5V - DIP	105.00	99.75	94.50	89.25	84.00
TEC6A101D2V	Max Output current 6 A, internal net. voltage across TEC 2.0V - DIP	105.00	99.75	94.50	89.25	84.00
TEC6A101D5V-XC-YC	Output 6 A, X = lower temp. limit Y = upper voltage across TEC 5.0V temp. limit window temperature range is 10°C to 40°C Dip package					
TEC6A101D4V-XC-YC	Output 6 A, X = lower temp. limit Y = upper voltage across TEC 4.0V temp. limit window temperature range is 10°C to 40°C Dip package					
TEC6A101D3.5V-XC-YC	Output 6 A, X = lower temp. limit Y = upper voltage across TEC 3.5V temp. limit window temperature range is 10°C to 40°C Dip package					
TEC6A101D3V-XC-YC	Output 6 A, X = lower temp. limit Y = upper voltage across TEC 3.0V temp. limit window temperature range is 10°C to 40°C Dip package					



	TEC6A101D2.5V-XC-YC	Output 6 A, X = lower temp. limit Y = upper voltage across TEC 2.5.0V temp. limit window temperature range is 10°C to 40°C Dip package					
	TEC6A101D2V-XC-YC	Output 6 A, X = lower temp. limit Y = upper voltage across TEC 2.0V temp. limit window temperature range is 10°C to 40°C Dip package					
	TEC-24V10A1	Output Voltage: 24V, Output Current: 10A	320.00	304.00	288.00	272.00	256.00
	ATA12A50V1	High efficiency high power AC input TEC controller, $I_{out_max} = 12A$, $V_{out_max} = 50V$	560.00	540.00	510.00	480.00	420.00
	ATW5V2.5V311D2A	Adjustable Set-point Temperature Window. 2 Amps DIP package.	88.00	83.00	78.00	73.00	
	ATW5V2.5V311D2P5A	Adjustable Set-point Temperature Window. 2.5 Amps DIP package.	88.00	83.00	78.00	73.00	
	ATW5V2.5V311D4A	Adjustable Set-point Temperature Window. 4 Amps DIP package.	98.00	93.00	88.00	83.00	
	ATW01-D	window controller setting TLLIM and TULIM to 0.1V to 2.9V respective window temperature range is 10°C to 40°C Dip package	20.00	18.00	16.00	15.00	14.00
	ATW01-S	window controller setting TLLIM and TULIM to 0.1V to 2.9V respective window temperature range is 10°C to 40°C SMT package	20.00	18.00	16.00	15.00	14.00
N	TECA1-5V-5V-D-Buffer						
			1-9	≥10			
	TECEV104	Complete tunable compensation network and application circuit for our TECA1 series	35.00	31.50			

TEC Modules (Peltier device)

			1 - 4	5 - 24	25-999	≥1000	
	ATE1-15-R6A	Imax 0.6A Vmax 2.1V Q max 0.62W Tdmax 70°C	28.00	26.60	25.20	23.80	
	ATE1-18-IR2A	Imax 1.2A Vmax 2.18V Q max 1.46W Tdmax 67°C	13.00	12.35	11.70	11.05	
	ATE1-48-3A	Imax 3.0A Vmax 5.69V Q max 9.5W Tdmax 67°C	10.00	9.50	9.00	8.50	
	ATE1-48-4A	Imax 3.9A Vmax 5.69V Q max 12.4W Tdmax 67°C	10.00	9.50	9.00	8.50	
	ATE1-49-4A	Imax 3.9A Vmax 5.6V Q max 12.4W Tdmax 70°C	10.00	9.50	9.00	8.50	
	ATE1-31-5A	Imax 5.5A Vmax 3.8V Q max 12W Tdmax 67°C	10.00	9.50	9.00	8.50	
	ATE1-49-5A	Imax 5A Vmax 5.6V Q max 17.7W Tdmax 67°C	10.00	9.50	9.00	8.50	
	ATE1-48-6A	Imax 6A Vmax V Q max W Tdmax °C	10.00	9.50	9.00	8.50	
	ATE1-63-3A	Imax 3A Vmax V Q max W Tdmax °C	10.00	9.50	9.00	8.50	
	ATE1-71-3A	Imax 3A Vmax 8.5V Q max 15.8W Tdmax 65°C	10.00	9.50	9.00	8.50	
	ATE1-71-4A	Imax 4A Vmax 8.5V Q max 21.1W Tdmax 65°C	10.00	9.50	9.00	8.50	
	ATE1-71-5A	Imax 5A Vmax 8.5V Q max 26.8W Tdmax 65°C	10.00	9.50	9.00	8.50	
	ATE1-71-3B	Imax 3.0A Vmax 8.5V Q max 16.6W Tdmax 67°C	10.00	9.50	9.00	8.50	
	ATE1-71-5B	Imax 5.0A Vmax 8.5V Q max 29.1W Tdmax 67°C	10.00	9.50	9.00	8.50	
	ATE1-71-6A	Imax 6.0A Vmax 8.5V Q max 34.1W Tdmax 67°C	10.00	9.50	9.00	8.50	



ATE1-71-7A	Imax 7.0A Vmax 8.5V Q max 40.3W Tdmax 65°C	10.00	9.50	9.00	8.50	
ATE1-127-2A	Imax 2.0A Vmax 15.4V Q max 20.0W Tdmax 66°C	12.00	11.40	10.80	10.20	
ATE1-127-3A	Imax 3.0A Vmax 15.4V Q max 25.0W Tdmax 67°C	12.00	11.40	10.80	10.20	
ATE1-127-4A	Imax 4.0A Vmax 15.4V Q max 33.4W Tdmax 67°C	12.00	11.40	10.80	10.20	
ATE1-127-3B	Imax 3.0A Vmax 15.4V Q max 25.0W Tdmax 65°C	12.00	11.40	10.80	10.20	
ATE1-127-4B	Imax 4.0A Vmax 15.4V Q max 35.0W Tdmax 65°C	12.00	11.40	10.80	10.20	
ATE1-127-5A	Imax 5.0A Vmax 15.4V Q max 44.5W Tdmax 65°C	12.00	11.40	10.80	10.20	
ATE1-127-5B	Imax 5.0A Vmax 15.4V Q max 44.5W Tdmax 65°C	12.00	11.40	10.80	10.20	
ATE1-127-6A	Imax 6.0A Vmax 15.4V Q max 53.3W Tdmax 65°C	12.00	11.40	10.80	10.20	
ATE1-127-8A	Imax 8.0A Vmax 15.4V Q max 71.0W Tdmax 65°C	14.00	13.30	12.60	11.90	
ATE1-127-9A	Imax 9.0A Vmax 15.4V Q max 80.0W Tdmax 65°C	14.00	13.30	12.60	11.90	
ATE1-127-17A	Imax 17.0A Vmax 15.4V Q max W Tdmax 65°C	18.00	17.10	16.20	15.30	
ATE1-127-18A	Imax 18.0A Vmax 15.4V Q max 170W Tdmax 65°C	18.00	17.10	16.20	15.30	
ATE1-127-24A	Imax 24.0A Vmax 15.4V Q max 226W Tdmax 65°C	18.00	17.10	16.20	15.30	
ATE1-127-24B	Imax 24.0A Vmax 15.4V Q max 226W Tdmax 65°C	18.00	17.10	16.20	15.30	
ATE1C-25-1R8A	Imax 1.8A Vmax 3.0V Q max 3.1W Tdmax 66°C	24.00	22.80	21.60	20.40	
ATE1C-48-1R8A	Imax 1.8A Vmax 5.8V Q max 6.0W Tdmax 66°C	30.00	28.50	27.00	25.50	
ATE1C-83-1R8A	Imax 1.8A Vmax 10V Q max 10.4W Tdmax 66°C	35.00	33.20	31.50	29.70	

SMD Component Kits

	Super Surface Mount 1% Resistor Kits	1				
	R12E96-50	510 values 1206 size 50PC/Value Resistor Kit	309.00			
	R12E96-100	510 values 1206 size 100PC/Value Resistor Kit	369.00			
	R12E96-200	510 values 1206 size 200PC/Value Resistor Kit	439.00			
S	R12E96-500	510 values 1206 size 500PC/Value Resistor Kit	629.00			
	R12E24-50	128 values 1206 size 50PC/Value Resistor Kit	89.00			
	R12E24-100	128 values 1206 size 100PC/Value Resistor Kit	109.00			
	R12E24-200	128 values 1206 size 200PC/Value Resistor Kit	139.00			
	R12E24-500	128 values 1206 size 500PC/Value Resistor Kit	189.00			
	R08E96-50	510 values 0805 size 50PC/Value Resistor Kit	299.99			
	R08E96-100	510 values 0805 size 1000PC/Value Resistor Kit	349.00			
	R08E96-200	510 values 0805 size 200PC/Value Resistor Kit	419.00			
S	R08E96-500	510 values 0805 size 500PC/Value Resistor Kit	599.00			
	R08E24-50	128 values 0805 size 50PC/Value Resistor Kit	89.00			
	R08E24-100	128 values 0805 size 100PC/Value Resistor Kit	99.00			
	R08E24-200	128 values 0805 size 200PC/Value Resistor Kit	109.00			
	R08E24-500	128 values 0805 size 500PC/Value Resistor Kit	169.00			



	R06E96-50	510 values 0603 size 50PC/Value Resistor Kit	289.00				
	R06E96-100	510 values 0603 size 100PC/Value Resistor Kit	339.00				
	R06E96-200	510 values 0603 size 200PC/Value Resistor Kit	399.00				
S	R06E96-500	510 values 0603 size 500PC/Value Resistor Kit	489.00				
	R06E24-50	128 values 0603 size 50PC/Value Resistor Kit	86.00				
	R06E24-100	128 values 0603 size 100PC/Value Resistor Kit	96.00				
	R06E24-200	128 values 0603 size 200PC/Value Resistor Kit	109.00				
	R06E24-500	128 values 0603 size 500PC/Value Resistor Kit	169.00				
	R04E96-50	510 values 0402 size 50PC/Value Resistor Kit	309.00				
	R04E96-100	510 values 0402 size 100PC/Value Resistor Kit	359.00				
	R04E96-200	510 values 0402 size 200PC/Value Resistor Kit	429.00				
S	R04E96-500	510 values 0402 size 500PC/Value Resistor Kit	519.00				
	R04E24-50	128 values 0402 size 50PC/Value Resistor Kit	89.00				
	R04E24-100	128 values 0402 size 100PC/Value Resistor Kit	109.00				
	R04E24-200	128 values 0402 size 200PC/Value Resistor Kit	129.00				
	R04E24-500	128 values 0402 size 500PC/Value Resistor Kit	189.00				
		Differential resistor Kits					
N	R08E96-50-300PCD	0805 1% 510 values. dependig on value 50 or 300 Pieces per value	419.00				
N	R06E96-50-300PCD	0603 1% 510 values. dependig on value 50 or 300 Pieces per value	399.00				
N	R04E96-50-300PCD	0402 1% 510 values. dependig on value 50 or 300 Pieces per value	429.00				
		Super Surface Mount 5% Resistor Kits					
	R06E24-50-5(5%)	128 values 0603 size 50PC/Value Resistor Kit 5%	159.00				
	R06E24-100-5(5%)	128 values 0603 size 100PC/Value Resistor Kit 5%	179.00				
	R06E24-200-5(5%)	128 values 0603 size 200PC/Value Resistor Kit 5%	199.00				
	R08E24-50-5(5%)	128 values 0805 size 50PC/Value Resistor Kit 5%	159.00				
	R08E24-100-5(5%)	128 values 0805 size 100PC/Value Resistor Kit 5%	179.00				
	R08E24-200-5(5%)	128 values 0085 size 200PC/Value Resistor Kit 5%	199.00				
		Super Surface Mount Capacitor Kits					
	C12-50	1206 size, 112 value, 50pc/value capacitor kit	158.00				
	C12-100	1206 size, 112 value, 100pc/value capacitor kit	208.00				
S	C12-200	1206 size, 112 value, 200pc/value capacitor kit	308.00				
S	C12-500	1206 size, 112 value, 500pc/value capacitor kit	598.00				
	C08-50	0805 size, 83 Values, 50PC/Value Capacitor Kit	148.00				
	C08-100	0805 size, 83 Values, 100PC/Value Capacitor Kit	188.00				
	C08-200	0805 size, 83 Values, 200PC/Value Capacitor Kit	258.00				
	C08-500	0805 size, 83 Values, 500PC/Value Capacitor Kit	428.00				
	C906-50	0603 size, 79 Values, 50PC/Value Capacitor Kit	138.00				
	C906-100	0603 size, 79 Values, 100PC/Value Capacitor Kit	178.00				



	C906-200	0603 size, 79 Values, 200PC/Value Capacitor Kit	218.00				
	C906-500	0603 size, 79 Values, 500PC/Value Capacitor Kit	338.00				
	C04-50	0402 size, 70 values, 50pc/value Capacitor kit	138.00				
	C04-100	0402 size, 70 values, 100pc/value Capacitor kit	178.00				
S	C04-200	0402 size, 70 values, 200pc/value Capacitor kit	238.00				
S	C04-500	0402 size, 70 values, 500pc/value Capacitor kit	338.00				
	T-C-25	Tantalum capacitor Kits 45values, 0.1uF-100uF, 25pc/value	119.00				
		Super Surface Mount Inductor Kits	1				
	L074V04-20	0402 size, 74 values 20pc Inductor kits	177.00				
	L074V04-50	0402 size, 74 values 50pc Inductor kits	267.00				
	L074V04-100	0402 size, 74 values 1000pc Inductor kits	407.00				
	L088V06-20	0603 size, 88 values 20pc Inductor kits	197.00				
	L088V06-50	0603 size, 88 values 50pc Inductor kits	317.00				
	L088V06-100	0603 size, 88 values 100pc Inductor kits	497.00				
	L085V08-20	0805 size, 85 values 20pc Inductor kits	197.00				
	L085V08-50	0805 size, 85 values 50pc Inductor kits	317.00				
	L085V08-100	0805 size, 85 values 100pc Inductor kits	497.00				
	L060V10-20	1008 size, 60 values 200pc Inductor kits	187.00				
	L060V10-50	1008 size, 60 values 50pc Inductor kits	257.00				
	L060V10-100	1008 size, 60 values 100pc Inductor kits	387.00				
	L06-10-35		97.00				
	L04-10-43		147.00				
		Super Surface Mount Enclosures and Labels	1-47	≥48			
	SK-128	128 cells with cap Empty enclosure	24.00	22.00			
	SK128A	128 cells with cap Empty enclosure	28.00	25.00			
	L-130	130 Empty labels for Empty Enclosure	1.00				

Flashlights

			1				
	FL8011	Light Source: 1W LED, Beam Color: white, Power Source: AA Battery * Maximum Size: 20 mm * 95 mm	8.00				
	FL8012	Light Source: 1W LED, Beam Color: white, Power Source: AA Battery * Maximum Size: 20 mm * 95 mm.	8.00				
	FL8013	Light Source: 1W LED, Beam Color: white, Power Source: AA Battery * Maximum Size: 20 mm * 95 mm	8.00				
	FL8014	Light Source: 1W LED, Beam Color: white, Power Source: AA Battery * Maximum Size: 20 mm * 95 mm	8.00				
	LH-9015	Light Source: μ5 LED, Beam Color: white, Power Source: AG13 Button Cell*3, Maximum Size: 5 mm * 68 mm, Weight:19.4 g	8.00				

